

**Detailed Specifications & Technical Data**



**8760 Paired - Audio, Control and Instrumentation Cable**

	<p><b>For more information please call</b>  <b>1-800-Belden1</b></p> <p><u>See Put-ups and Colors</u></p>
---	---

**Description:**

18 AWG stranded (16x30) tinned copper conductors, twisted pair, polyethylene insulation, overall 100% Beldfoil® shield, 20 AWG stranded tinned copper drain wire, PVC jacket.

**PHYSICAL CHARACTERISTICS:**

**CONDUCTOR:**

Number of Pairs	1
Total Number of Conductors	2
AWG	18
Stranding	16x30
Conductor Material	TC - Tinned Copper

**INSULATION:**

Insulation Material	PE - Polyethylene
Nom. Insulation Wall Thickness	.019 in.
Lay Length	1.5 in.
Twists/ft.	8

Pair Color Code Chart :

Number	Color
1	Black & Clear

**OUTER SHIELD:**

Outer Shield Material Trade Name	Beldfoil®
Outer Shield Type	Tape
Outer Shield Material	Aluminum Foil-Polyester Tape w/Shorting Fold
Outer Shield % Coverage	100 %

**OUTER SHIELD DRAIN WIRE :**

Outer Shield Drain Wire AWG	20
Outer Shield Drain Wire Stranding	Stranded
Outer Shield Drain Wire Conductor Material	TC - Tinned Copper

**OUTER JACKET:**

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

**Detailed Specifications & Technical Data**



**8760 Paired - Audio, Control and Instrumentation Cable**

Outer Jacket Nominal Wall Thickness	.028 in.
-------------------------------------	----------

**OVERALL NOMINAL DIAMETER:**

Overall Nominal Diameter	.222 in.
--------------------------	----------

**MECHANICAL CHARACTERISTICS:**

Operating Temperature Range	-20°C To +60°C
UL Temperature Rating	60°C (UL AWM Style 2092)
Bulk Cable Weight	26.6 lbs/1000 ft.
Max. Recommended Pulling Tension	62 lbs.
Min. Bend Radius (Install)	2.25 in.

**APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:**

**APPLICABLE STANDARDS:**

NEC/(UL) Specification	CM
CEC/C(UL) Specification	CM
AWM Specification	UL Style 2092 (300 V 60°C)

**FLAME TEST:**

UL Flame Test	UL1581 Vertical Tray
---------------	----------------------

**PLENUM/NON-PLENUM:**

Plenum (Y/N)	N
Plenum Number	88760, 87760 or 82760

**ELECTRICAL CHARACTERISTICS:**

Nom. Characteristic Impedance	60 Ohms
Nom. Inductance	.18 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	24 pF/ft
Nom. Cap. Cond. to Other Cond. & Shield @ 1 KHz	44 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	6.5 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS (UL AWM Style 2092)
Max. Recommended Current	5.2 Amps per conductor @ 25°C

**PUT-UPS AND COLORS:**

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
8760 0601000	2 #18 LDPE SH PVC	1000	26	CHROME	C
8760 06010000	2 #18 LDPE SH PVC	10000	260	CHROME	C Y
8760 0602000	2 #18 LDPE SH PVC	2000	50	CHROME	C
8760 060250	2 #18 LDPE SH PVC	250	6.75	CHROME	

**Detailed Specifications &  
Technical Data**



**8760 Paired - Audio, Control and Instrumentation Cable**

8760 060500	2 #18 LDPE SH PVC	500	13	CHROME	C
8760 0605000	2 #18 LDPE SH PVC	5000	135	CHROME	C
8760 060U1000	2 #18 LDPE SH PVC	U1000	26	CHROME	
8760 060U500	2 #18 LDPE SH PVC	U500	13	CHROME	

C = CRATE REEL PUT-UP.

Y = FINAL PUT-UP LENGTH MAY VARY -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

Revision Number: 1      Revision Date: 11-04-2004

© 2003 Belden Wire & Cable Company  
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.